



Bellofram Silicones, Inc.
 a division of The Marsh Bellofram
 Group of Companies

8019 Ohio River Blvd
 Newell, WV 26050 USA
 Ph: 304-387-1200
 Fax: 304-387-1289
 siliconesRFQ@bellofram.com

6704 Commercial Grade Solid Silicone Rubber Extruded Products

DESCRIPTION

The Bellofram Silicones 6704 is a 70 Shore “A” durometer solid silicone commercial grade rubber elastomer product, available in both standard and custom extruded profiles. They are designed for applications in which superior physical properties are not required, yet where resistance to temperature extremes is important.

Contact us at siliconesRFQ@bellofram.com for a product sample or quotation.



FEATURES

- Excellent gasketing material
- Resistance to temperature extremes
- Ultraviolet ray (UV) resistant
- Ozone resistant
- Non-toxic

MATERIAL SPECIFICATIONS

- ASTM D2000 M1GE705

TYPICAL PHYSICAL PROPERTIES

| PROPERTY | TEST METHOD | SPECIFICATION |
|---|-------------|---------------------|
| Durometer | Shore "A" | 70 ± 5 |
| Tensile, MPa (psi) | | 820 |
| Compression Set (22 Hours @ +175°C) | | 42% |
| Oil Immersion (IRM 903 70 Hours @ +150°C) | | Volume change, +41% |
| Temperature Resistance (Continuous) (°F) | | -85° to +400 °F |

Data noted above is based on laboratory tests and should be used as a reference only. Further information and additional specifications are available upon request. Tests, claims, representations, and descriptions regarding flammability are based on standard laboratory tests, and they may not be reliable for determining, evaluating, predicting, or describing the flammability or burning characteristics under actual fire conditions, whenever used alone or in combination with other products. Accordingly, each potential user should make an individual determination whether the flammability or burning characteristics of the product are suitable for the purpose intended by the user.