



Bellofram Silicones, Inc.
a division of The Marsh Bellofram
Group of Companies

8019 Ohio River Blvd
Newell, WV 26050 USA
Ph: 304-387-1200
Fax: 304-387-1289
siliconesRFQ@bellofram.com

BELLOFOAM™ 7605 CLOSED CELL SILICONE SPONGE SHEETING

DESCRIPTION

The Bellofram Silicones BELLOFOAM™ 7605 is a lightweight, closed-cell silicone sponge sheeting material, developed to ASTM D-1056 2D0 material specifications. The sheets are designed for use within a wide variety of applications and environments.

Product is available in 36 square inch (914.4 square millimeter) sheets, ranging in thickness from 0.125" to 2.00" (3.175 to 50.8 mm).

Contact us at siliconesRFQ@bellofram.com to request a free product sample or quotation.



FEATURES

- Lightweight
- Resistance to temperature extremes
- Excellent gasket material
- Low closure force
- Very low compression set
- Ultraviolet ray (UV) resistant
- Ozone resistant
- Non-conductive insulating material

MATERIAL SPECIFICATIONS

- ASTM D-1056 2D0

TYPICAL PHYSICAL PROPERTIES

Color		Red
25% Compression Deflection	ASTM D-1056	0 to 2 psi
50% Compression Set (22 Hours @ +212°F/+100°C)	ASTM D-1056	6%
Density (max.)	ASTM D-1056	10 lbs/ft ³
Water Absorption	ASTM D-1056	10% max.
Flammability	FMVSS 302	Pass
Temperature Resistance (continuous)		-85° to +400°F

Data noted above is based on laboratory tests and should be used as a reference only. Further information and additional specifications are available upon request. Tests, claims, representations, and descriptions regarding flammability are based on standard laboratory tests, and they may not be reliable for determining, evaluating, predicting, or describing the flammability or burning characteristics under actual fire conditions, whenever used alone or in combination with other products. Accordingly, each potential user should make an individual determination whether the flammability or burning characteristics of the product are suitable for the purpose intended by the user.