

T350 Filter

Excellent Filtration

The element is made from high efficiency glass microfiber with high grade 316SS end caps and support cages.

Filter complies with NACE MR1075 for sulfide stress cracking resistant metallic material for oil field equipment

Maintenance

A tight seal is guaranteed by the use of a thread element connection. The filter housing and element have been polished and degreased. No special lubricants are needed in the field for replacing the element.

The element is threaded into the housing so there is no need for extra parts during installation or maintenance of the filter. There is no chance of losing top or bottom seals or rings required for installation.

Applications

- Filtering Supply Gas
- Filtering Air Supply

T350 Part Matrix

T3500200000	000	
	↑	Drain Valve Option
	P	Plug
	V	Manual Drain Valve
	000	
Replacement Element		971-350-000

Flow Rates

Body Size	Pressure Differential	SCFM
1/4 NPT	5 PSIG	19 SCFM
	10 PSIG	27 SCFM
	20 PSIG	40 SCFM

Specifications

Body Size	1/4 NPT	
Max Operating Pressure	4000 PSIG	
Max Operating Temperature	248 ° F	120 ° C
Drain Valve Assemble Options	Plugged Drain Port	
	Manual Drain Valve	
Weight Approximate	1.1 lb	0.5 kg
Materials of Construction		
Body,	Stainless Steel NACE Construction	
Filter	25 Micron Glass Microfiber	
	Stainless Filter End Caps	

T350 Dimensions

